

COLD DRAWN ROUNDS

C1018, C1045, C1144 Stress Relieved

Lengths - 12' 20'

Size	Lbs./Ft.	Lbs./20'
1/8	0.042	0.84
3/16	0.094	1.88
1/4	0.167	3.34
5/16	0.261	5.22
3/8	0.376	7.52
7/16	0.511	10.22
1/2	0.668	13.36
9/16	0.845	16.90
5/8	1.040	20.80
11/16	1.260	25.20
3/4	1.500	30.00
13/16	1.760	35.20
7/8	2.040	40.80
15/16	2.350	47.00
1	2.670	53.40
1 1/16	3.020	60.40
1 1/8	3.380	67.60
1 3/16	3.770	75.40
1 1/4	4.170	83.40
1 5/16	4.600	92.00
1 3/8	5.050	101.00
1 7/16	5.520	110.40
1 1/2	6.010	120.20
1 9/16	6.520	130.40
1 5/8	7.050	141.00
1 3/4	8.180	163.60
1 7/8	9.390	187.80
1 15/16	10.020	200.40
2	10.680	213.60
2 1/8	12.060	241.20
2 3/16	12.780	255.60
2 1/4	13.520	270.40
2 3/8	15.060	301.20
2 7/16	15.870	317.40
2 1/2	16.690	333.80
2 3/4	20.190	403.80
2 15/16	23.040	460.80
3	24.030	480.60
3 7/16	31.550	631.00
3 1/2	32.710	654.20
4	42.730	854.60