

Expanded Metal

Style Designation	Lbs./ Sq. Ft.	Size of Opening in Inches		Center to Center of Bridges in Inches		Size of Strands in Inches		
		Plain	Width	Length	Width	Length	Width	Length
1/2 - 13	1.47		5/16	15/16	0.500	1.2	0.92	0.096
3/4 - 13	0.80		13/16	1 11/16	0.923	2.0	0.092	0.096
3/4 - 9	1.80		3/4	1 9/19	0.923	2.0	0.134	0.150
1 1/2 - 9	1.20		11/16	1 3/8	1.330	3.0	0.134	0.144
1 1/2 - 6	2.50	1	1/8	2 5/16	1.330	3.0	0.198	0.203

Flattened Expanded Metal

Style Designation	Lbs./ Sq. Ft.	Size of Opening in Inches		Center to Center of Bridges in Inches		Approximate Thickness of Strands in Inches	
		Plain	Width	Length	Width		Length
1/4 - 18	1.11		3/32	11/16	0.255	1.031	0.040
1/2 - 18	0.66		9/32	1	0.500	1.260	0.039
1/2 - 16	0.82		1/4	1	0.500	1.260	0.050
1/2 - 13	1.40		1/4	1 3/4	0.500	1.260	0.070
3/4 - 13	0.75		11/16	1 25/32	0.923	2.120	0.070
3/4 - 9	1.71		9/16	1 11/16	0.923	2.120	0.120
1 1/2 - 13	0.57	1	1/16	2 3/4	1.330	3.200	0.070
1 1/2 - 9	1.14	1		2 9/16	1.330	3.200	0.120

Walkway, Skywalk, & Grating

Style Designation	Lbs./ Sq. Ft.	Size of Opening in Inches		Center to Center of Bridges in Inches		Size of Strands in Inches		
		Plain	Width	Length	Width	Length	Width	Length
Walkway	4.27	1		2 7/8	1.412	4.00	0.250	0.300
Skywalk	3.14	1	5/8	4 7/8	2.000	6.00	0.250	0.312
3.0 lb. Grating	3.00		15/16	3 7/16	1.333	5.33	0.183	0.264
4.0 lb. Grating	4.00		15/16	3 7/16	1.333	5.33	0.215	0.300
5.0 lb. Grating	5.00		15/16	3 3/8	1.333	5.33	0.250	0.331
6.25 lb. Grating	6.25		15/16	3 3/8	1.410	5.33	0.312	0.350